

GUARDIAN®

CR3 CABLE SRL

Self-Retracting Lifeline

The CR3 33 ft SRL is part of Guardian's strongest SRL lineup in the industry. This Class 1 SRL is both lightweight and durable to help take on our customer's toughest tasks. This SRL includes an ergonomic carry handle for mobility on the jobsite and is designed to attach to an anchor point at or above a worker's dorsal D-ring.

Class
1
Anchor at or above dorsal D-ring

HEIGHT SAFETY. SIMPLIFIED.

guardianfall.com

CR3 CABLE SRL

Self-Retracting Lifeline



Class 1
Anchor at or above dorsal D-ring

Key features & benefits

Swivel top connection point
Swivels 360 degrees to ensure the device remains in the best orientation during use and also helps prevent lifeline snagging or tangling. Double locking carabiner included.

Thermoplastic housing
Super lightweight & durable for long lasting use in the toughest applications

QR code enabled labels
Easy access to product information

Rubber lifeline stopper
Doubles as a convenient hand-grip

Steel cable lifeline
Resists cuts and abrasions

Fall-indicating swivel snap hook
Shows if SRL has been exposed to to an impact

Integrated Handle
Allows for user comfort when carrying and installing the SRL

Specifications

User weight range (including tools and equipment) | ANSI 130-310 lb | OSHA 100-420 lb
Max. Arresting Force | 1,800 lb
Ave. Arresting Force | 1,150 lb
Max. Arresting Distance | 42″
Max. Allowable Free Fall | Not Permitted
Min. Required Free Clearance | 7 ft
Permitted Service Temperature | -40º to 130º F
Materials | Aluminum, stainless steel, galvanized steel, & rubber

Hook Options



Steel swivel snap hook

Part number(s)	Description	Hook type	Length	OSHA User Weight Range	ANSI User Weight Range
4200220	CR3, Cable, Class 1	Steel swivel snap hook	33′	100-420 lb	130-310 lb

Declaration of conformity
This product has been tested in an ISO 17025 accredited laboratory in accordance with all requirements specified by ANSI Z359.7.

This product conforms with the following safety regulations and consensus standard:
OSHA 1910.140 & 1926.502 | **ANSI ANSI Z359.14-2021**

For more information:
+1 (800) 466 6385
info@guardianfall.com

Designed and tested in the **United States**