GUARDIAN®
FALL PROTECTION

SCAFFOLD CHOKER

ANCHORAGE CONNECTOR

TECHNICAL DATA SHEET - ISSUE 1

DURABLE 1" POLYESTER WEBBING
Withstands repeated use for long life



PULL-THROUGH INSTALL
Easily attaches to scaffold or other compatible structural members up to 4" in diameter.



GALVANIZED STEEL D-RING
Resists corrosion

Materials: Polyester and Galvanized Steel
Capacity Range: 130-420 lbs.
Overall Length: 17"
Minimum Breaking Strength: 5,000 lbs.

FOR MORE INFO, PLEASE CALL **1.800.466.6385** OR VISIT **GUARDIANFALL.COM**

PSG
PURE SAFETY GROUP

PROD CODE
#01641

SCAFFOLD CHOKER

ANCHORAGE CONNECTOR

TECHNICAL DATA SHEET - ISSUE 1

Standards

• ANSI Z359.18-2017 • ANSI A10.32-2012 • OSHA 1910.140 • OSHA 1926.502



Performance:

- Type A anchorage connector
- Maximum Users: 1
- Minimum Breaking Strength (MBS): 5,000 lbs.
- Minimum Service Temperature: -30° F
- Accomodates compatible structures up to 4" in diameter

Notes:

- Suitable for use with horizontal lifelines.
- Never connect to closed loop.

Applications

Personal Fall Arrest: Scaffold Choker may be used to support a MAXIMUM 1 PFAS for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.

Restraint: Scaffold Choker may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side (Pairs only).

PROD CODE

#01641