PRODUCT SPECIFICATION & TECHNICAL DATA

IUS151 - Ultrasoft 9oz Suit-All Bottom

Collection: IFR
Shell Fabric: Westex®: 88% FR Cotton, 12% Nylon, 305g
Outer Carton: 15



Product information

FEATURES • Engineered for flame resistance and guaranteed for the life of the garment • 50% extended garment wear life over 100% cotton • Soft feel of cotton comfort • Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure • H2S monitor can attach to outside of pocket with strap and elastic fasteners STANDARDS • Westex UltraSoft® fabric meets the requirements of: NFPA 2112, CGSB 155.20, NFPA 70E, CSA Z462, ASTM F1506

IFR

IFR

Standards

NFPA® 2112
NFPA® 70E
ASTM F1506
CGSB 155.20
CSA Z462
CSA-Z96 Class 1 (Level FR)
ASTM F1959 (ATPV 12.4 CAL/CM^2)

Features

- Engineered for flame resistance and guaranteed for the life of the garment
- Soft feel of Cotton comfort
- Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure
- H2S monitor can attach to outside of pocket with strap and elastic fasteners

PRODUCT SPECIFICATION & TECHNICAL DATA

IUS151 - Ultrasoft 9oz Suit-All Bottom
Commodity Code:

Test House

Wash care



Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m^3)	EAN13	DUN14
IUS151RBR34		39.0	29.0	39.0	0.7710	0.0441		
IUS151RBR36		39.0	29.0	39.0	0.7940	0.0441		
IUS151RBR38		39.0	29.0	39.0	0.7940	0.0441		
IUS151RBR40		39.0	29.0	39.0	0.8160	0.0441		
IUS151RBR42		39.0	29.0	39.0	0.8620	0.0441		
IUS151RBR44		39.0	29.0	39.0	0.8850	0.0441		
IUS151RBR46		39.0	29.0	39.0	0.8850	0.0441		
IUS151RBR48		39.0	29.0	39.0	0.9300	0.0441		
IUS151RBR50		39.0	29.0	39.0	0.9070	0.0441		
IUS151RBR54		39.0	29.0	39.0	1.0210	0.0441		
IUS151RBR58		39.0	29.0	39.0	1.0890	0.0441		