Technical Data Sheet

Heat Shrink Tubing – 5/8" x 10' ID – 2:1 Ratio – Single Wall Polyolefin – Flexible – Flame Retardant

Brand / manufacturer	Kable Kontrol
Product category	Shrinking Tube
Product codes	SKU: RS-HS358-S10

Product description

Kable Kontrol 2:1 single-wall polyolefin heat shrink tubing, 5/8 in x 10 ft.

Key benefits

- Flexible, flame retardant (except clear), cross-linked polyolefin
- Shrinks to 50% of original diameter; 5–7% lengthwise shrinkage
- Resists chemicals and oils
- UL listed (E536025); RoHS compliant

Typical applications

- Electrical insulation, wire bundling, colour coding, strain relief, identification and braided sleeving ends

Specifications

Size (ID x length)	5/8 in x 10 ft
Shrink ratio	2:1
Shrink temp.	194°F (90°C)
Operating temp.	-67°F to 275°F (-55°C to 135°C)
Rating	600 V

Information source

Russmill Safety product listing — https://www.russmillsafety.com/products/heat-shrink-tubing-5-8-x-10-id-2-1-ratio-single-wall-polyolefin-flexible-flame-retardant (listing notes product information supplied by the manufacturer, Kable Kontrol)

Prepared by Russmill Safety from publicly available manufacturer information and our product listing. This is not the manufacturer's original publication. For legally required safety data, use the manufacturer's official Safety Data Sheet.

Prepared by Russmill Safety · November 2026

Supplier / distributor contact

Supplier / distributor	Russmill Safety
Store	A1 Queen’s Highway, Suite 2–3, Freeport, Grand Bahama F42190, The Bahamas
USA warehouse (fulfilment)	1526 NW 23rd Avenue, Fort Lauderdale, FL 33311
Phone	Bahamas customer service +1 242 351 7623 · USA +1 954 333 8542 · Freeport store +1 242 688 3336
Email	customerservice@russmillsafety.com (customer service) · sales@russmillsafety.com (sales enquiries)
Website	https://www.russmillsafety.com