Technical Data Sheet

Pneumatic double diaphragm pump, 1.5 inch - 35GPM and Max 120PSI

Product category	Pump
Product codes	SKU: QBK-40 UPC: 722047766786

Product description

Air-operated double diaphragm pump, 1.5 in, 35 GPM.

Key benefits

- Polypropylene body with PTFE (Teflon) diaphragms; extra diaphragm set included
- No lubrication; no sparks; can run dry
- Flow and head adjustable by valve; submersible

Typical applications

- Waste oil, fuels, solvents, slurries, sewage, coolants and DEF
- Petroleum, mining, paint, printing, water treatment and automotive

Specifications

Max. flow	35 GPM
Max. pressure	120 psi
Max. head	226.4 ft / 69 m
Max. temperature	150°F / 66°C
Port	1.5 in

Product information supplied by the manufacturer.

Information source

Russmill Safety product listing — https://www.russmillsafety.com/products/pneumatic-double-diaphragm-pump-1-5-inch-35gpm-and-max-120psi

Supplier / distributor contact

Supplier / distributor	Russmill Safety
Store	A1 Queen’s Highway, Suite 2–3, Freeport, Grand Bahama F42190, The Bahamas
USA warehouse (fulfilment)	1526 NW 23rd Avenue, Fort Lauderdale, FL 33311
Phone	Bahamas customer service +1 242 351 7623 · USA +1 954 333 8542 · Freeport store +1 242 688 3336
Email	customerservice@russmillsafety.com (customer service) · sales@russmillsafety.com (sales enquiries)
Website	https://www.russmillsafety.com